

## Pressure Transmitter XY-PTMT200

### Typical Feature

- Small size for mount design, minimum size M5\*1
- High-precision maximum accuracy 0.25% FS
- Temperature stability index 0.02%/FS/ °C
- Wide measurement field, even corrosion, easy crystallize medium
- Stainless Steel material with fully sealed structure
- Customized structure diversification is available












### Brief Introduction

XY-PTMT200 Pressure Transmitter is with small size, which can be minimum M5\*1. Special design and precision machining technology make it with excellent dynamic and static qualities; Stainless steel shell and laser-welded construction, IP65 or IP67 Ingress protection; Ultrathin and small pressure transmitter/transducer can be used in specific environment if the work condition is limited about test point size, or need to keep flow distribution. XUYAN offer customized type to against harsh rugged work condition by customer special requirements.

The Small size mounted type Precision Pressure Transmitter has excellent performance such as high precision, fast response, small size, light-weight, stable and reliable, strong overload capacity; designed for most medium in industry, such as air, oil, water and other fluid; Micro pressure transmitter is mainly applied in the followed situations: aerodynamics, aircraft and engine experiment, wind tunnel experiment, hydromechanics experiment, hydraulic modeling experiment, biomedicine experiment, chemical explosive and nuclear explosive blast experiment; Output 4 ~ 20mA or 0 ~ 5VDC standard electrical signal through regulation device; Measurement Range: 0-5 Kpa,0-100 Kpa,0-8000KPa. Thoughtful specialized electric circuit design, it's easy to install in microprocessor intelligent control system; calibrated by ultra-high precision absolute pressure calibration equipment, accuracy 0.2%; 0.5%; temperature stability index can be increased to 0.02%/FS/C by sensor temperature self-compensation and specialized circuit debugging.

### Suggested Applications

-  Aerodynamics
-  Aircraft & Engine Experiment,
-  Wind Tunnel Experiment,
-  Hydromechanics Experiment,
-  Hydraulic Modeling Experiment
-  Biomedicine Experiment,
-  Chemical Explosive
-  Nuclear Explosive Blast
-  Experiment Specification

**More details for XY-PTMT200, please contact us.**

Specification

Model	XY-PTMT		
	100	200	300
Gauge Pressure Range	0~5...100...1000KPa	0~5...100...8000KPa	Air pressure 0~20...200KPa Others 0~1...10...50...100MPa
Pressure Type	Gauge Pressure Test		
Measurement Medium	Gas or Liquid with Compatibility of SS 304, SS316 or Silicon		
Accuracy	0.2%FS; 0.5%FS additional conditioning circuit		
Long-Term Stability/Year	±0.2%FS/Year		
Zero Temperature Drift	Typical: ±0.02%FS/°C; Maximum ±0.05%FS/°C		
Sensitivity Temperature Drift	Typical: 0.02% FS / °C; The Maximum: 0.05% FS / °C		
Overload Pressure	200%		
Operation Temperature	-30~80 °C		
Compensation Temperature	-10~70 °C		
Environmental Temperature	-40~ 120 °C		
Power Supply	5VDC		
Overvoltage Protection	≤3X; ≤5X; ≤10X (by Range)		
Signal Output	mV (>30mA@Full Scale)		
Response Time	Depend on measurement range and structure		
IP Protection Class	IP65; IP67		

Performance Parameter

Performance Parameter	A	B	C	D
Non-linear/±%FS	1.00	0.50	0.20	0.1
Non-redundant, hysteria /±%FS	0.20	0.15	0.10	0.04
Zero temperature coefficient/X10 <sup>-4</sup> /°C.FS	5.00	3.00	2.00	1.00
Sensitivity temperature coefficient/X10 <sup>-4</sup> /°C.FS	5.00	3.00	2.00	1.00
Zero time drift/%FS/8h	0.20	0.15	0.10	0.10
Accuracy%FS	1.00	0.50	0.25	0.15

Dimension(mm)

Mode	Size
XY-PTMT100	Φ 3mm-Φ8mm
XY-PTMT200	M5*1-M10*1
XY-PTMT300	Φ 10*5mm-Φ30*10mm

## How To Order

XY-PT		G		KF		4M		1		A		P2		M3		B1		T1		L	
		Type		Pressure Connection		Pressure Range		Accuracy		Output		Power		Thread		Electrical Connection		dium Temperatu		Additional	
G	General	None	General	XK	(0-XkPa)	1	0.15%	A	4-20mA	P1	5V	M1	M20*1.5	A	HIRSCHMANN	T1	-20~80°C	L	With Display		
GA	Absolute Pressure	P	Diaphragm Seals	XB	(0-XBa)	2	0.25%	R	RS485	P2	24V	M2	G1/4	B	Cable Outlet	T2	-20~120°C	I	Explosion-Proof		
DP	Differential Pressure	DP	Differential Pressure	XM	(0-XMPa)	3	0.50%	V1	0-10V	P3	12-28V	M3	G1/2	C	Circular Connector	T3	0~150°C				
GR	IoT	KF	Clamp	CC	Customized	4	1.00%	V2	0-5V	P6	12V	M4	1/2NPT	CC	Customized	T9	Customized				
GT	Temperature & Pressure	DN	Flange			9	Customized	V3	0.5-4.5V	P9	Customized	M5	1/4NPT								
MT	Mini Thickness	1210	Explosion Proof					CC	Customized			M7	ZG1/4								
MK	Economic	9999	Customized									M9	Customized								
HF	High Frequency																				
A	Air Conditioning																				
B	Ink Corrosion Resistance																				
C	Air Compressor																				
M	Hydraulic Pressure																				
W	Water Pressure																				

### Shanghai Xuan Precision Technology Co., Ltd.

**Address:** No. 969, Yunshan Road Pudong District Shanghai City China

**Tel:** +86 21 59241315

**Email:** sales@xvyanprecision.com

**Website:** [www.xvyanprecision.com](http://www.xvyanprecision.com)

**Product Manager:** Tyler Tou

**Cell:** +86 189 1797 0680

**Email:** ttao@Xuyanpercision.com